

Stratum

Stratum Square panels are high density gypsum boards in 4 types of patterns. The panel width and border perimeters varies depending on the installation type and desired pattern effect.

STRATUM SQUARE

PERFORMANCE



A 2-21, D0 (non-flammable)
according to DIN EN 13501




Maximum Relative Humidity: 70%




Recycled Content: 86% (3% Post Consumer)



NRC: Up to .85




Cavity Depth 2.5" Felt Only	0.15	0.30	0.60	0.80	0.60	0.40
Cavity Depth 8" Felt Only	0.45	0.60	0.70	0.65	0.60	0.45
Cavity Depth 2.5" with 2" fiberglass	0.40	0.65	0.75	0.70	0.65	0.50
Cavity Depth 8" with 2" fiberglass	0.55	0.80	0.85	0.70	0.70	0.60



Joints are filled with **GypSorb Ready Mix** joint compound then skimmed over with **standard finishing compound**. Once dry, the joints are sanded smooth in order to receive prime and paint. See *Sonus/Strata Installation Principles* for further information.

100% size to show pattern



CHARACTERISTICS

Perforation Type:	Square
Board Thickness:	1/2" (12.5mm)
Non-woven Fabric Backing:	White
Finish:	Unfinished paper face
Open Area:	7.8% - 13.0%
Weight:	1.76 lbs / s.f.

AVAILABLE BOARD SIZES

900mm x 2700mm (~35.43" x 106.3") ☐

1200mm x 2400mm (~47.24" x 94.49") ☐

